

Preliminary 132

risen

Hyper-ion Ultra

Heterojunction Hyper-ion Series Bifacial Module

RSM132-8-740-760BHDG

Hyper-link Interconnection

Patented Technology

740-760 W_p

Power Output Range

24.5%

Higher Efficiency

0~+3%

Positive Power Tolerance

The module picture is for reference only



No B-O caused LID



Ultra-high bifacial factor



Ultra-high power generation, ultra-low carbon emission



Most stable power temperature coefficient



Lead technology of metallization process



Excellent anti-LID & anti-PID performance




* As there are different certification requirements in different markets, please contact your local Risen Energy sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

LINEAR PERFORMANCE WARRANTY


15 years product warranty / 30 years linear power warranty

0.3% Annual Degradation over 30 years



*Please check the valid version of Limited Product Warranty which is officially released by Risen Energy Co., Ltd

Dimensions of PV Module



*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

ELECTRICAL DATA (STC)

Model Type	RSM132-8-740-760BHDG				
Rated Power in Watts-Pmax(Wp)	740	745	750	755	760
Open Circuit Voltage-Voc(V)	50.47	50.54	50.60	50.68	50.75
Short Circuit Current-Isc(A)	18.56	18.65	18.74	18.83	18.92
Maximum Power Voltage-Vmpp(V)	42.32	42.38	42.44	42.50	42.56
Maximum Power Current-Impp(A)	17.50	17.59	17.68	17.77	17.86
Module Efficiency (%) *	23.8	24.0	24.1	24.3	24.5

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

Bifacial factor: 90±5(%) * Module Efficiency (%): Rounding to the nearest number

ELECTRICAL DATA (BNPI)

Model Type	RSM132-8-740-760BHDG				
Maximum Power-Pmax (Wp)	830	835	841	846	852
Open Circuit Voltage-Voc (V)	50.47	50.54	50.60	50.68	50.75
Short Circuit Current-Isc (A)	20.81	20.91	21.01	21.11	21.21
Maximum Power Voltage-Vmpp (V)	42.32	42.38	42.44	42.50	42.56
Maximum Power Current-Impp (A)	19.60	19.71	19.81	19.91	20.02

BNPI: Front side irradiance 1000 W/m², Rear side irradiance 135 W/m², Cell Temperature 25°C, Air Mass AM1.5.

Power measurement tolerance: ±3%

Electrical characteristics with 10% rear side power gain

Total Equivalent power -Pmax (Wp)	814	820	825	831	836
Open Circuit Voltage-Voc(V)	50.47	50.54	50.60	50.68	50.75
Short Circuit Current-Isc (A)	20.42	20.52	20.61	20.71	20.81
Maximum Power Voltage-Vmpp(V)	42.32	42.38	42.44	42.50	42.56
Maximum Power Current-Impp(A)	19.25	19.35	19.45	19.55	19.65

Rear side power gain: The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.



MECHANICAL DATA

Solar cells	n-type HJT
Cell configuration	132 cells (6×11+6×11)
Module dimensions	2384×1303×33mm (93.86×51.30×1.30 in)
Weight	38.5kg (84.88 lb)
Superstrate	2.0mm(0.08in), High Transmission, AR Coated Heat Strengthened Glass
Substrate	2.0mm(0.08in), Heat Strengthened Glass
Frame	GFRP, Black
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm ² , 350mm(13.78 in)(+), 230mm(9.06 in)(-), connector Included, or customized length
Connector	PV-SY02/Others
Maximum mechanical test load	5400 Pa (front) / 2400 Pa (back), under certain installation method

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	43°C±2°C
Temperature Coefficient of Voc	-0.22%/°C
Temperature Coefficient of Isc	0.047%/°C
Temperature Coefficient of Pmax	-0.24%/°C
Level T ₉₅ ≤ 70°C	-40°C~+70°C *
Maximum System Voltage	1500VDC
Max Series Fuse Rating	35A
Limiting Reverse Current	35A

* Short-term up to 85°C; higher operation requires IEC TS 63126 testing



PACKAGING CONFIGURATION

	40ft(HQ)
Number of modules per container	594
Number of modules per pallet	33
Number of pallets per container	18
Packaging box dimensions (LxWxH) in mm	1320×1125×2520
Box gross weight[kg]	1322

risen

RISEN ENERGY CO., LTD.

Tashan Industry Zone, Meilin, Ninghai 315609, Ningbo | PRC

Tel: +86-574-59953239

Fax: +86-574-59953599

E-mail: marketing@risen.com

Website: www.risen.com

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© 2026 Risen Energy. All rights reserved. Contents included in this datasheet are subject to change without notice.

No special undertaking or warranty for the suitability of special purpose or being installed in extraordinary surroundings is granted unless as otherwise specifically committed by manufacturer in contract document.

Version: REM132-BHDG-08B-EN-H2-1-2026-Ultra-GFRP

THE POWER OF RISING VALUE